

G-1/1.2/1.5/2/3

Glass Capillary

General type of glass capillary.

ø1mm ~ ø3mm O.D. glass capillaries are available for forming various shapes of electrodes. G-1, G-1.2, and G-1.5 are pre-washed in an ultrasonic washing machine.



GD-1/1.2/1.5/2

Glass Capillary with Filament

Ultrasonic cleaned glass capillary with a filament.

These are glass capillaries with a filament inside. The filament leads the liquid up to the capillary tip. They are pre-washed in an ultrasonic washing machine.



GC-1/1.2/1.5

Glass Capillary

Box of 200 (5 each to a vacuum packed bag).

These glass capillaries are pre-washed in an ultrasonic washing machine, and sterilized with ultraviolet ray. They are vacuum packed to protect against dust and dirt.



GDC-1/1.2/1.5

Glass Capillary with Filament

Box of 200 (5 each to a vacuum packed bag).

These are glass capillaries with a filament inside. The filament leads the liquid up to the capillary tip. They are pre-washed in an ultrasonic washing machine, sterilized with ultraviolet ray, and vacuum-packed.



G-100

Thin-walled Glass Capillary

Ultrasonic cleaned thin-walled glass capillary.

This thin-walled glass capillary has been prewashed in an ultrasonic washing machine. The smaller outer diameter in thin-walled glass capillary helps to diminish damage to cells.



G-1000

Glass Rod

Ultrasonic cleaned glass rod.

This glass rod has high intensity so that it is used as a microtool for boring a small hole in cells or cutting out a sample in micro dissection. Prewashed in an ultrasonic washing machine.



G/GD/GC/GDC/G-100/G-1000

Glass Capillary & Glass Rod

Specification

Type	<u>G-1</u>	<u>G-1.2</u>	<u>G-1.5</u>	<u>G-2</u>	<u>G-3</u>	<u>GD-1</u>	<u>GD-1.2</u>	<u>GD-1.5</u>	<u>GD-2</u>
Outer diameter (mm)	1	1.2	1.5	2	3	1	1.2	1.5	2
Inner diameter (approx. mm)	0.6	0.75	0.9	0.8	1.8	0.6	0.75	0.9	1.2
Length (mm)	90*	90*	90*	90*	90	90*	90*	90*	90*
Contents (pcs)	500	500	500	200	200	500	500	500	200
Material	Borosilicate								

Type	<u>GC-1</u>	<u>GC-1.2</u>	<u>GC-1.5</u>	<u>GDC-1</u>	<u>GDC-1.2</u>	<u>GDC-1.5</u>	<u>G-100</u>	<u>G-1000</u>
Outer diameter (mm)	1	1.2	1.5	1	1.2	1.5	1	1
Inner diameter (approx. mm)	0.6	0.75	0.9	0.6	0.75	0.9	0.75	-
Length (mm)	90	90	90	90	90	90	90*	90*
Contents (pcs)	200	200	200	200	200	200	500	200
Material	Borosilicate							

* A custom length between 70mm and 180mm is also available by special order.

Specifications are subject to change without notice.

Copyright © NARISHIGE Group. All Rights Reserved. 1999-2017